during the reporting period, this information shall be reported to the responsible Agreement State agency upon request of the agency.

(c) The person shall maintain all information concerning transfers and receipts of devices that supports the reports required by this section. Records required by this paragraph must be maintained for a period of 3 years following the date of the recorded event.

[65 FR 79189, Dec. 18, 2000, as amended at 68 FR 58805, Oct. 10, 2003; 73 FR 5719, Jan. 31, 2008]

§ 32.53 Luminous safety devices for use in aircraft: Requirements for license to manufacture, assemble, repair or initially transfer.

An application for a specific license to manufacture, assemble, repair or initially transfer luminous safety devices containing tritium or promethium-147 for use in aircraft, for distribution to persons generally licensed under §31.7 of this chapter, will be approved if:

- (a) The applicant satisfies the general requirements specified in §30.33 of this chapter;
- (b) The applicant submits sufficient information regarding each device pertinent to evaluation of the potential radiation exposure, including:
- (1) Chemical and physical form and maximum quantity of tritium or promethium-147 in each device;
- (2) Details of construction and design:
- (3) Details of the method of binding or containing the tritium or promethium-147;
- (4) Procedures for and results of prototype testing to demonstrate that the tritium or promethium-147 will not be released to the environment under the most severe conditions likely to be encountered in normal use;
- (5) Quality assurance procedures to be followed that are sufficient to ensure compliance with §32.55:
- (6) Any additional information, including experimental studies and tests, required by the Commission to facilitate a determination of the safety of the device.
- (c) Each device will contain no more than 10 curies of tritium or 300 millicuries of promethium-147. The lev-

els of radiation from each device containing promethium-147 will not exceed 0.5 millirad per hour at 10 centimeters from any surface when measured through 50 milligrams per square centimeter of absorber.

- (d) The Commission determines that:
- (1) The method of incorporation and binding of the tritium or promethium-147 in the device is such that the tritium or promethium-147 will not be released under the most severe conditions which are likely to be encountered in normal use and handling of the device:
- (2) The tritium or promethium-147 is incorporated or enclosed so as to preclude direct physical contact by any person with it:
- (3) The device is so designed that it cannot easily be disassembled; and
- (4) Prototypes of the device have been subjected to and have satisfactorily passed the tests required by paragraph (e) of this section.
- (e) The applicant shall subject at least five prototypes of the device to tests as follows:
- (1) The devices are subjected to tests that adequately take into account the individual, aggregate, and cumulative effects of environmental conditions expected in service that could adversely affect the effective containment of tritium or promethium-147, such as temperature, moisture, absolute pressure, water immersion, vibration, shock, and weathering.
- (2) The devices are inspected for evidence of physical damage and for loss of tritium or promethium-147, after each stage of testing, using methods of inspection adequate for determining compliance with the criteria in paragraph (e)(3) of this section.
- (3) Device designs are rejected for which the following has been detected for any unit:
- (i) A leak resulting in a loss of 0.1 percent or more of the original amount of tritium or promethium-147 from the device; or
- (ii) Surface contamination of tritium or promethium-147 on the device of more than 2,200 disintegrations per minute per 100 square centimeters of surface area; or
- (iii) Any other evidence of physical damage.

§ 32.54

(f) The device has been registered in the Sealed Source and Device Registry.

[30 FR 8192, June 26, 1965, as amended at 33 FR 6463, Apr. 27, 1968; 43 FR 6923, Feb. 17, 1978; 77 FR 43693, July 25, 2012]

§ 32.54 Same: Labeling of devices.

(a) A person licensed under §32.53 to manufacture, assemble, or initially transfer devices containing tritium or promethium-147 for distribution to persons generally licensed under §31.7 of this chapter shall, except as provided in paragraph (b) of this section, affix to each device a label containing the radiation symbol prescribed by §20.1901 of this chapter, such other information as may be required by the Commission including disposal instructions when appropriate, and the following or a substantially similar statement which contains the information called for in the following statement: 1

The receipt, possession, use, and transfer of this device, Model* ______, Serial No.* ____, containing ______ (Identity and quantity of radioactive material) are subject to a general license or the equivalent and the regulations of the U.S. NRC or of a State with which the NRC has entered into an agreement for the exercise of regulatory authority. Do not remove this label.

CAUTION—RADIOACTIVE MATERIAL

(Name of manufacturer, assembler, or initial transferor.)*

*The model, serial number, and name of manufacturer, assembler, or initial transferor may be omitted from this label provided they are elsewhere specified in labeling affixed to the device.

- (b) If the Commission determines that it is not feasible to affix a label to the device containing all the information called for in paragraph (a) of this section, it may waive the requirements of that paragraph and require in lieu thereof that:
- (1) A label be affixed to the device identifying:
- (i) The manufacturer, assembler, or initial transferor; and
- (ii) The type of radioactive material; and
- ¹Devices licensed under §32.53 prior to January 19, 1975 may bear labels authorized by the regulations in effect on January 1, 1975.

- (2) A leaflet bearing the following information be enclosed in or accompany the container in which the device is shipped:
- (i) The name of the manufacturer, assembler, or initial transferor,
- (ii) The type and quantity of radioactive material,
 - (iii) The model number,
- (iv) A statement that the receipt, possession, use, and transfer of the device are subject to a general license or the equivalent and the regulations of the U.S. NRC or of an Agreement State, and
- (v) Such other information as may be required by the Commission, including disposal instructions when appropriate.

[33 FR 16331, Nov. 7, 1968, as amended at 40 FR 8785, Mar. 3, 1975; 43 FR 6923, Feb. 17, 1978; 63 FR 39483, July 23, 1998]

§ 32.55 Same: Quality assurance, prohibition of transfer.

- (a) Each person licensed under §32.53 shall visually inspect each device and shall reject any that has an observable physical defect that could adversely affect containment of the tritium or promethium-147.
- (b) Each person licensed under §32.53 shall:
- (1) Maintain quality assurance systems in the manufacture of the luminous safety device in a manner sufficient to provide reasonable assurance that the safety-related components of the distributed devices are capable of performing their intended functions; and
- (2) Subject inspection lots to acceptance sampling procedures, by procedures specified in paragraph (c) of this section and in the license issued under §32.53, to provide at least 95 percent confidence that the Lot Tolerance Percent Defective of 5.0 percent will not be exceeded.
- (c) The licensee shall subject each inspection lot to:
- (1) Tests that adequately take into account the individual, aggregate, and cumulative effects of environmental conditions expected in service that could adversely affect the effective containment of tritium or promethium-147, such as absolute pressure and water immersion.